



ANSUL® Foam System Solutions



The power behind **your mission**





About ANSUL® Products

The ANSUL® brand has served the global firefighting industry since 1939 with high-quality, field-proven products, expert technical service, innovative R&D, and customized solutions for challenging fire hazards. The ANSUL® portfolio of foam concentrates and engineered equipment provides a comprehensive range of fire protection solutions for fixed and semi-fixed system installations, plus emergency response capability.

In addition to foam systems, the ANSUL® brand offers a full line of special hazard fire protection products including fire extinguishers and hand-line units; pre-engineered restaurant and vehicle systems; sophisticated sprinkler and fire detection/suppression systems; and dry chemical and gaseous extinguishing agents. ANSUL® products are developed and tested at the ANSUL® Fire Technology Center, one of the most extensive fire research and testing facilities in the world.

ANSUL® Foam Systems

Our complete line of firefighting foam products is one of the most extensive in the industry. As a global manufacturer of both concentrates and hardware, ANSUL® foam products and systems are 3rd-party tested, rated, approved or certified to multiple industry standards, including:

- UL 162
- UL 139
- ULCS564/560
- FM 5130
- US DOD MIL-PRF-24385
- US Coast Guard
- ICAO Levels B&C
- IMO 1312
- EN1568-2008



ANSUL® Foam System applications include:

Aviation

- Aircraft Hangars
- Airports
- Heliports
- Maintenance Bays
- Engine Test Facilities

Industrial

- Chemical Plants
- Hazardous Material Spills
- Blending Operations
- Power Plants
- Waste Treatment
- Pumping Stations
- Truck Loading Racks
- Warehouses

Marine and Offshore

- Engine and Pump Rooms
- Cargo Holds
- Helidecks
- Offshore Platforms
- FPSOs and FSOs
- Jetties
- Dry Docks
- Onshore - Offshore Storage

Oil, Gas and Petrochemical

- Refineries
- Tank Farms, Storage Tanks and Dikes
- Petrochemical Facilities
- LNG Terminals
- Pipelines

Foam Concentrates

ANSUL® foam concentrates are formulated and tested for fire and vapor suppression on a wide range of challenging hazards. Our concentrates are subject to stringent quality controls, from incoming raw materials inspection to finished product testing. ANSUL® concentrates intended for system application include AFFF, AR-AFFF, and Fluoroprotein concentrates for low- and medium-expansion systems, and JET-X concentrates for medium- and high-expansion systems.



Foam Testing Services

Foam concentrate properties and performance may decline over time, even when stored under optimal conditions. Many industry standards require annual foam testing, and our regional foam laboratories – located in the United States, Singapore, and Germany – provide fast turnaround for most foam analyses. Please contact your regional sales representative for information on foam concentrate sample testing.

ANSULITE Aqueous Film-Forming Foam (AFFF) concentrates combine fluoro- and hydrocarbon surfactant technologies to produce high performance firefighting foams for use on Class B hydrocarbon fuels such as oil, petroleum, gasoline, benzene, diesel, and aviation fuels.

ANSULITE Alcohol Resistant Aqueous Film-Forming Foam (AR-AFFF) concentrates combine AFFF surfactant technology with a polymeric membrane for use on both Class B polar solvent fuels – such as alcohols and ketones – as well as hydrocarbon fuel fires.

ANSUL® Fluoroprotein (FP) and Fluoroprotein Alcohol Resistant (FPAR) concentrates are produced from naturally-occurring hydrolyzed proteins with fluorochemical additives to deliver a robust, aspirated foam blanket with high heat stability and good burnback resistance. FP concentrates are applicable for fire and vapor suppression on Class B hydrocarbon fuel fires, and FPAR foam may be used on both hydrocarbon and polar solvent fires.



Additional ANSUL® non-fluorinated offerings for firefighting emergency response and training include:

- SILV-EX PLUS and ANSUL-A foam concentrates for Class A fire suppression
- TARGET-7 agent for vapor mitigation and hazard pH neutralization
- Training Foam concentrate to simulate 3% or 6% AFFF for training (non-firefighting) purposes only
- ABC, BC and Purple K dry chemicals for twin agent fire suppression



Concentrate Selection Guide for Low/Medium-Expansion Foam Systems

ANSUL® Foam Concentrate	Proportioning Rate		Application Type				Approvals, Listings & Standards												
	Fuel Type						UL	ULC		FM	US DOD	USCG	EN-1568:2008				ICAO		IMO 1312
	Hydro-carbon	Polar	Aviation	Marine	Industrial	Low Temp	162	S564	S560	5130	MIL-PRF -24385	162.033	Part				Level		Med B/D
													1	2	3	4	B	C	
AFFF																			
AFC1B	1%				✓		✓	✓											
AFC1B-FP29	1%		✓		✓	✓	✓	✓											
AFC3B	3%				✓		✓	✓		✓									
AFC-3MS	3%		✓		✓		✓	✓			✓								
AFC-3DC	3%		✓		✓					✓									
AFC3IB2	3%		✓		✓												✓		
AFC3IC1	3%		✓		✓		✓	✓										✓	
AFC3B-FP29	3%		✓		✓	✓	✓	✓									✓		
AFC6B	6%				✓		✓	✓											
AFC-6MS	6%		✓		✓		✓	✓			✓								
AFC-6DC	6%		✓		✓					✓									
AFC6IB2	6%		✓		✓												✓		
AFC6IC1	6%		✓		✓		✓	✓										✓	
AR-AFFF																			
A111-FP18	1%	1%			✓	✓	✓	✓					✓		✓	✓			
A137	1%	3%			✓		✓	✓					✓		✓	✓			
A137-FP18	1%	3%			✓	✓	✓	✓											
A335	3%	3%			✓		✓	✓					✓		✓	✓			
A334-LV	3%	3%			✓		✓	✓		✓					✓	✓			
A336 USCG	3%	3%		✓	✓		✓	✓				✓							
A337-FP13	3%	3%	✓	✓	✓	✓							✓	✓	✓	✓	✓		✓
A364	3%	6%			✓		✓	✓											
FLUOROPROTEIN																			
AFP3B	3%			✓	✓		✓	✓					✓		✓				✓
AFP6B	6%				✓		✓	✓					✓		✓				
AFPAR331-FP15	3%	3%	✓	✓		✓							✓		✓	✓	✓		✓

Refer to the latest product technical data sheet for additional physiochemical properties and application information.

Note: If any foam product is discharged into the environment, efforts should be made to control, contain and collect the discharge for proper disposal, while following all applicable laws, regulations, and codes. Further information regarding the use, discharge, and disposal of firefighting foams can be found at www.ansul.com

High-Expansion Foam Systems

ANSUL® JET-X High-Expansion (Hi-Ex) concentrates produce flexible firefighting foams for suppression of indoor and outdoor Class A, Class B, and LNG fires. With expansion ratios from 50:1 to 1000:1, our JET-X concentrates can quickly form substantial volumes of foam for large-capacity applications. Hi-Ex foams contain minimal water while quickly flooding over-sized rooms and enclosures, providing effective suppression of horizontal and vertical (three-dimensional) fires while minimizing water damage.

JET-X concentrates are non-fluorinated formulations optimized for performance when paired with JET-X high-expansion foam generators:

- JET-X 2% Hi-Ex concentrate is formulated for use with fresh water only at a 2% proportioning rate and is UL Listed, FM Approved, and EN1568:2008, Part 1 certified.
- JET-X 2¾% concentrate is UL Listed and may be proportioned with fresh, salt, or hard water, which makes it well-suited for marine applications.

JET-X high-expansion foam systems are used for fire and vapor suppression in large enclosures containing high value property such as aircraft hangars, distribution warehouses, marine/engine pump rooms, and tunnels. They may also be used in open space applications such as flammable liquid storage areas and LNG facilities.





JET-X foam systems provide fire suppression solutions for a multitude of special hazards. The portfolio offers UL Listed, FM Approved configurations, design flexibility for utilization of inside or outside air supply, and specific generator models for LNG hazards. All JET-X generators are CE Marked in conformance with the Machinery Directive 2006/42/EC.

The ANSUL® Portable Foam Generator, with optional smoke extraction unit, provides mobile application of Hi-Ex foam for smaller-scale hazard responses. Typical applications include:

- Blanketing LNG spill fires
- Controlling vapor release from liquid spills
- Inerting tanks
- Suppressing fire and vapors in ship holds and engine rooms



ANSUL® Hi-Ex Systems Listings & Approvals

JET-X Generator	JET-X 2% Concentrate					JET-X 2¾% Concentrate				
	UL	FM	Application Type			UL	Application Type			
			Aviation	Industrial	LNG		Marine	Aviation	Industrial	LNG
2A	139		✓	✓		139	✓	✓	✓	
5A	139	5130	✓	✓		139	✓	✓	✓	
15A	139	5130	✓	✓		139	✓	✓	✓	
20	139		✓	✓		139	✓	✓	✓	
27	139	5130	✓	✓			✓	✓	✓	
3	139		✓	✓				✓	✓	
2A LNG	139				✓					✓
5A LNG	139									✓
20 LNG	139				✓					✓

Refer to the latest product technical data sheet for additional mechanical, material, and physiochemical properties and application information.

Fixed and Semi-Fixed Systems for Low/Medium-Expansion Foam

Our extensive portfolio of firefighting foam products provides comprehensive protection for flammable liquid hazards.

Proportioners

In addition to bladder tank systems, the wide array of ANSUL® proportioning equipment provides a calibrated ratio of foam concentrate to water for a host of application, specification and certification requirements.

The UL Listed / FM Approved FLOWMAX PPW variable range proportioner mitigates the need for multiple, different-sized IBPs.

Around-The-Pump proportioners provide a simple and effective means to introduce the desired foam concentrate percentage to the water being discharged from a firefighting pump system.

When used in conjunction with atmospheric concentrate storage tanks, Balanced Pressure Pump proportioning skids maintain equal pressure in the foam concentrate and water inlets, allowing operation over a wide range of flows and pressures.

The ANSUL® foam proportioning product line includes:

- In-line balanced pressure proportioners for variable flows/pressures
- Around-the-pump inductors for a consistent foam mixture
- Cost-effective inline inductors
- Self-inducing nozzles for easy installation and use





Bladder Tank Systems

ANSUL® Bladder tanks are a key component of a complete balanced pressure proportioning system. These pressure-rated tanks contain an internal elastomeric bladder that stores the foam concentrate.

Upon system actuation, pressurized water propels the concentrate from the bladder to the system proportioning device. The proportioner meters the concentrate into the firefighting water line to create the

foam solution, which is then piped to the system discharge device(s) positioned to protect the hazard area.

Configurable ANSUL® bladder tanks range from 50 to 3000 gallons (189 to 11356 liters) with multiple available options, and they are UL Listed with a variety of foam concentrates. FM Approved systems are qualified with ANSULITE AFC3B 3% AFFF, A334-LV 3x3 AR-AFFF, or JET-X 2% Hi-Ex foam concentrate, in conjunction

with specified ANSUL® proportioners and discharge devices. ANSUL® bladder tanks up to 800 gallons (3028 liters) meet the minimum requirements for Seismic Zone 4 earthquake resistant design as calculated per the 1997 Uniform Building Code.

Designed and manufactured for rapid delivery, these systems include a variety of features that make installation, service and maintenance efficient and convenient.

Configurable options for ANSUL® bladder tanks include:

- Foam Concentrate Volume
- Trim Piping Material
- Paint Color
- Corrosion Resistance
- Sight gauges
- Thermal Pressure Relief Valves
- Pre-piped / Skid-Mounted
- Horizontal or Vertical Orientation

ANSUL® Bladder Tank Selection Guide

ANSUL® Bladder Tank Design					System Listings, Approvals, Ratings, Certifications				
Pre-Piped	Capacity		Orientation		ASME Sec VIII, Div 1	UL	FM	CE Marked	Seismic Zone 4
	Gallons	Liters	Horizontal	Vertical					
Standard	25-36	95-136		✓	175 psi	162	5130		
Optional	50	189		✓	175 psi	162	5130		✓
	100-200	379-757	✓	✓	175 psi	162	5130		✓
	300-800	1136-3028	✓	✓	175 psi	162	5130	✓	✓
	900-2000	3407-7571	✓	✓	175 psi	162	5130	✓	
	2200-3000	8328-11356	✓	✓	175 psi	162	5130	✓	

For complete approved system requirements refer to product technical datasheets and respective agency standard, listing and/or approval manual.

Monitors



Foam monitors are designed to control the horizontal and vertical delivery of large capacity discharge streams from a distance. The ANSUL® product line offers a wide range of monitor sizes with a host of features, including adjustable oscillation, variable spray patterns and multiple control options. ANSUL® monitors may be mounted to a fixed system, a mobile skid, or an emergency response vehicle for firefighting flexibility.

Options and configurations for ANSUL® monitors include:

- Flow Capacity – Up to 5300 gallons per minute (20062 liters/minute)
- Throw Range – Up to 400 feet (122 meters)
- Flow – Adjustable Fog to Jet spray patterns, Foam or Water
- Power – Electric, Water, Hydraulic
- Control – Remote or Manual
- Targeting – Elevation, Rotation and Oscillation adjustment
- Mounting – Fixed or Mobile skid

Tank Protection



ANSUL® foam chambers and foam makers are air-aspirating foam discharge devices designed to protect flammable liquid storage tanks. These devices offer effective fire and vapor suppression options for most vertical tank configurations – cone, fixed, open, closed or floating roof design. These specialized discharge devices provide protection for hydrocarbon or polar solvent fuel tanks when coupled with the appropriate ANSULITE concentrate and foam system design.

ANSUL® tank protection solutions include:

- Fixed foam chambers for quick application of foam with minimal submergence and agitation of the fuel surface in storage tanks or diked areas
- Floating roof and area foam makers
- Rim seal foam pourers for floating roof tank
- High back-pressure foam makers for closed-roof storage tank subsurface injection systems

Design and Installation Services

We partner with our customers to deliver high-quality, top-performing fire suppression systems for many special hazard applications. Whether delivering a standard, configured or customized system, the ANSUL® Technical Service team draws upon decades of fire protection experience to provide knowledgeable assistance with:

- Design
- Specification
- Installation
- Commissioning
- Field Service
- Training





A Passion for Protection

Dedicated customer support. Extensive product portfolio. Engineering excellence. Trusted, proven brand. ANSUL® products offer all of these attributes, plus a passion for protection. It's what drives us to create solutions to help safeguard what matters most – your valued people, property and business.



About Johnson Controls

At Johnson Controls, we transform the environments where people live, work, learn and play. From optimizing building performance to improving safety and enhancing comfort, we drive the outcomes that matter most. We deliver our promise in industries such as healthcare, education, data centers and manufacturing. With a global team of 105,000 experts in more than 150 countries and over 130 years of innovation, we are the power behind our customers' mission. Our leading portfolio of building technology and solutions includes some of the most trusted names in the industry, such as Tyco®, York®, Metasys®, Ruskin®, Titus®, Frick®, Penn®, Sabroe®, Simplex®, Ansul® and Grinnell®.

For more information, contact your regional ANSUL® product representative or visit www.ansul.com.

Australia

Johnson Controls
Level 3
95 Coventry Street Southbank
VIC 3006
Australia
Tel: +61 3 9313 9700
FSP.InsideSales.ANZ@jci.com

China

7F, No. 40, Kailong Elite Building
1888 XinJinQiao Road,
Jinqiao Pudong Shanghai 201206
China
Tel: +86 21 6163 3373
FSP.InsideSales.CN@jci.com

Hong Kong

Johnson Controls
23/F, Exchange Tower
33 Wang Chiu Road,
Kowloon Bay, Kowloon,
Hong Kong
Tel: +852 2753 3012
FSP.InsideSales.SG@jci.com

India

Johnson Controls
1001, Wing "C",
10th Floor Godrej Coliseum, Sion Mumbai
400022
India
Tel: +91 22 6628 6628
FSP.InsideSales.IN@jci.com

Indonesia

Johnson Controls
Pondok Indah Office Tower 3 17th Floor, Jl.
Sultan Iskandar Muda V Pondok Indah, Jakarta
12310 Indonesia
Tel: +62 21 2953 8893
FSP.InsideSales.SG@jci.com

Korea

Johnson Controls
Shinil Bldg #205
#830-130 Beomil-Dong,
Dong-Gu Busan
48741, Korea
Tel: +82 51 638 8926
FSP.InsideSales.KR@jci.com

Singapore

Johnson Controls
2, Serangoon North Avenue 5
#07-01 554911
Singapore
Tel: +65 6577 4360
FSP.InsideSales.SG@jci.com

Taiwan

Johnson Controls
17/F, No. 77, Sec. 1
Xintai 5th Rd Xizhi Dist
New Taipei City 22101 Taiwan
R.O.C
Tel: +886 2 2698 3559 Ext. 811
FSP.InsideSales.SG@jci.com

United Arab Emirates

Johnson Controls
Internet City, Office Park Building #56 Block D,
Floor 3
Dubai
United Arab Emirates
Tel: +971 4 455 0700
FSP.InsideSales.AE@jci.com